

EXPLANATION OF THE PPP PROJECT PPP PROJECT OVERVIEW REVIEW THE FLYOVER LAYOUT

Jakarta, 23 November 2023

Head of Investment Cooperation Coordination Sub-directorate, Directorate Implementation of Road and Bridge Infrastructure Financing, DJPI Head of Subdirectorate for Investment Cooperation Coordination, DGIF

MINISTER FOR PUBLIC WORKS AND HUMAN SETTLEMENTS DIRECTORATE GENERAL OF PUBLIC WORKS AND HOUSING INFRASTRUCTURE FINANCE



URGENCY OF FLYOVER VIEW REVIEW



3 MAIN POINTS OF HAZARDS & RISKS

Location 1: Location with a bend radius of 80m (requirement: 95m)

Location 2: (Main Bottleneck): Panorama 1, namely the location with a bend radius of 7m, and vertical alignment 22% (requirement: 8%)

Location 3: Location with 14% vertical alignment (8% requirement)



PROJECT DESCRIPTION / PROJECT DESCRIPTION

Jalan Sitinjau Lauik is part of the route connecting Padang City and Solok City. However, the current geometric conditions of the road do not meet traffic safety and comfort standards. The bends in Sitinjau Lauik have a combination of horizontal and vertical geometry that is not ideal, with a small horizontal curve radius and a large vertical gradient, causing the risk of accidents and high vehicle operating costs. Improvements are needed to improve traffic safety and comfort in the area.



PROJECT PROFILE OF SITINJAU LAUIK FLYOVER



PPP SCHEME (PPP SCHEME)

Build for Handover (Built-Operate-Transfer / BOT)

Return Scheme Investment

Payment Availability

Return of Investment

FINAN		
nvestment Fee, Rp. Base unit price in October 023)*	2.824 Trillion	Investment Cost, IDR (Unit Price in October 2023)
Construction Costs, Rp.	1.996 Trillion (2023)	Construction Cost, IDR
Concession Period, years	12.5	Concession Period, year

TECHNICAL DATA / TECHNICAL DATA

Length, kilometers	2,781 km	Length, kilometers	
a. Bridge Construction	1.01km	Bridge Construction, kilometers	
b. Construction at grade	1.77km	At grade Construction, kilometers	
Design Speed, km/h	40 km/h	Design Speed, km/hour	
Number of Lanes, lanes	1 x 2 Lanes	Number of Lanes, lanes	
Lane Width, meters	3.5m	Lane Width, meters	
Normal transverse slope, meters	6-10%	Normal Cross Slope, meters	
Transverse slope normal outer road shoulder, meters	4%	Normal Cross Slope of Outer Shoulder Road, meters	
maximum superelevation, meters	8%	Maximum Superelevation, meters	
Sidewalk, meters	0.5m	Sidewalk, meters	

ROAD & BRIDGE WORK SCOPE / ROAD & BRIDGE SCOPE

Work Path
Road gradea): 1 - STA 0+000 to 0+077
Bridge 1 - STA 0+077 to 0+206
Road gradea): 2 - STA 0+206 to 0+472
Bridge 2 - STA 0+472 to 0+627

BRIDGE STRUCTURE TYPE

1. Bridge 1, Bridge 2, Bridge 3 2. Bridge 4

6. Road (7. at grades) 3 – STA 0+627 to 0+762 Bridge 3 – STA 0+762 to 1+175 8. Road (9. at grades) 4 – STA 1+175 to 1+760 Bridge 4 – STA 1+760 to 2+069 10. Road (at grades) 5 – STA 2+069 to 2+781

: Combination of Balance Cantilever + PCI Girder : Extradose



PROJECT PROFILE OF SITINJAU LAUIK FLYOVER



INDICATIVE PROJECT TIMELINE

F.S	PROCUREMENT	PQ	RfP	BID AWARD	CONTRACTS SIGNING	FINANCIAL CLOSE	CONSTRUCTION	OPERATIONS
Q2 2023	Q3 2023	Q1 2024	Q1 2024	Q2 2024	Q3 2024	Q4 2024	Q1 2025-Q2 2027	Q3 2027

THANK YOU